

## BCMA Series

Common Mode Filters For Automotive Signal Line  
Size 3216

### FEATURES

- 
- Common mode filters for Signal Line
- 
- AEC-Q200 qualified
- Quantity: 2000pcs


### APPLICATION

- interfaces (MOST, USB2.0, IDB-1394, etc.)







Dimensions: [mm]

Land Pattern: [mm]

Electrical Properties:



# Typical Electrical Characteristics:



## Soldering Reflow:

Preheat condition: 150 ~200°C / 60~120 sec.


Allowed time above 217°C: 60~150 sec.

Max temperature: 260°C.


## Packaging Information:

Tape Dimension :

Peel force of top cover tape:



Reel Dimension: [mm]



Packaging Quantity:

## Cautions and Warnings:

### Storage Conditions:

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max). If the storage period elapses, the soldering of the terminal electrodes may deteriorate. The warranty period is one year.
- Product should not be exposed to environment with high temperature, high humidity, dust, corrosive gas and etc.
- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- Please always handle products carefully to prevent any damage caused by dropping down or inappropriate removing.

### Operation Instructions:

- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Before soldering, be sure to preheat components. The preheating temperature should be set so that the
- 
-