



MDTA Series

Flat Wire Molded Inductor

Size 7030




FEATURES

- Flat wire coil for low copper losses
-
-
- High current capacity
- AE
-
-


APPLICATION

- Noise suppressor for motor wipers / power seats/
-
-

Dimensions: [mm]



Land Pattern: [mm]



Electrical Properties:


	(μ H)	±20%	(A)	(A)		(m)	(mm)
MDTA7030-1R0M	1.00	±20%	30.0	16.1	21.8	5.00	6.6±0.3
MDTA7030-1R5M	1.50	±20%	25.0	12.0	15.3	8.25	6.6±0.3
MDTA7030-2R2M	2.20	±20%	19.0	10.0	13.0	13.7	6.2±0.3
MDTA7030-2R7M	2.70	±20%	16.0	9.20	11.4	15.4	6.2±0.3
MDTA7030-3R3M	3.30	±20%	15.0	8.00	10.0	18.0	6.2±0.3
MDTA7030-4R7M	4.70	±20%	13.5	6.90	9.00	26.7	6.2±0.3
MDTA7030-5R6M	5.60	±20%	12.5	5.30	7.30	33.2	6.2±0.3
MDTA7030-6R8M	6.80	±20%	12.0	4.50	6.80	42.5	6.2±0.3
MDTA7030-8R2M	8.20	±20%	10.2	3.00	5.90	48.73	6.2±0.3

Saturation Current will cause L to drop approximately 30%


Temperature Rise Current that causes the specified temperature rise from 25°C ambient.




Reel Dimension: [mm]



2.2±0.5




Packaging Quantity:



1500 Pcs/Reel



2 Reel /Inner box(3000 Pcs)



3 Inner box/Carton box(9K Pcs)

Cautions and Warnings:

Storage Conditions:

-
-
-
-

Operation Instructions:

-
-
-
-